


Specifications

Trimble SPS361 Modular GPS Heading Receiver



Receiver Name	SPS361 GPS Heading Receiver
Configuration Option	DGPS
Type	Modular
Base and rover interchangeability	No, rover only
Base operation	NA
Rover operation	All models
Heading operation	All models ⁵
Rover position update rate	1 Hz, 2 Hz, 5 Hz, 10 Hz, 20Hz
Rover maximum range from base	Unlimited
Rover operation within a VRS™ network	DGPS only
Factory options	NA
General	
Keyboard and display	VFD display 16 characters by 2 rows On/Off key for one-button startup Escape and Enter keys for menu navigation 4 arrow keys (up, down, left, right) for option scrolls and data entry
Dimensions (L x W x D)	24 cm (9.4 in) x 12 cm (4.7 in) x 5 cm (1.9 in) including connectors
Weight	1.22 kg (2.70 lb) receiver only 1.34 kg (2.95 lb) receiver with internal beacon radio
Antenna Options	
GA510	L1/L2 GPS, SBAS, and OmniSTAR (optimized for OmniSTAR)
GA530	L1/L2 GPS, MSK Beacon, SBAS, and OmniSTAR not supported
L1/Beacon, DSM 232	L1/L2 GPS, SBAS, and OmniSTAR
Zephyr™ Model 2	L1/L2 GPS, SBAS, and OmniSTAR
Zephyr Geodetic™ Model 2	L1/L2 GPS, SBAS, and OmniSTAR
Zephyr Model 2 Rugged	L1/L2 GPS, SBAS, and OmniSTAR
Zephyr, Zephyr Geodetic, Z-Plus, Micro-Centered™	Refer to antenna specification
Temperature	
Operating	-40 °C to +65 °C (-40 °F to +149 °F) ¹
Storage	-40 °C to +80 °C (-40 °F to +176 °F)
Humidity	MIL-STD 810F, Method 507.4
Waterproof	IP67 for submersion to depth of 1 m (3.3 ft), dustproof
Shock and Vibration	
Drop	Designed to survive a 1 m (3.3 ft) pole drop onto a hard surface To 75 g, 6 ms
Shock – Non-operating	To 40 g, 10 ms, saw-tooth
Shock – Operating	
Vibration	Tested to Trimble ATV profile (4.5 g RMS): 10 Hz to 300 Hz: 0.04 g/Hz; ² 300 Hz to 1,000 Hz; -6 dB/octave

Specifications

Trimble SPS361 Modular GPS Heading Receiver

Measurements

Advanced Trimble Maxwell™ 5 Custom GPS chip
High-precision multiple correlator for L1/L2 pseudo-range measurements

Unfiltered, unsmoothed pseudo-range measurements data for low noise, low multipath error, low-time domain correlation, and high-dynamic response

Very low noise carrier phase measurements with <1 mm precision
in a 1 Hz bandwidth

L1/L2 signal-to-noise ratios reported in dB-Hz
Proven Trimble low elevation tracking technology
72-channel L1 C/A code, L1/L2 Full Cycle Carrier

Trimble EVEREST™ multipath signal rejection
2-channel MSK Beacon (Optional)
4-channel SBAS (WAAS/EGNOS/MSAS)

Code Differential GPS Positioning²

Correction type
Correction source
Horizontal accuracy
Vertical accuracy

DGPS RTCM 2.x
DGPS Base via radio or Internet
 $\pm(0.25\text{m} + 1 \text{ ppm})$ RMS $\pm(0.8 \text{ ft} + 1 \text{ ppm})$
 $\pm(0.50\text{m} + 1 \text{ ppm})$ RMS $\pm(1.6 \text{ ft} + 1 \text{ ppm})$

SBAS (WAAS/EGNOS/MSAS) Positioning³

Horizontal accuracy
Vertical accuracy

Typically <1 m (3.3 ft)
Typically <5 m (16.4 ft)

OmniSTAR Positioning

VBS service accuracy
XP service accuracy
HP service accuracy

Horizontal <1 m (3.3 ft)
NA
NA

Location RTK Positioning²

Horizontal accuracy
Vertical accuracy

NA
NA

Precise Heading

Heading accuracy
2 m antenna separation
10 m antenna separation

0.09° RMS
0.05° RMS

Power

Internal
NA

External

Power input on the 26-pin D-sub connector is optimized for Trimble lithium-ion battery input with a cut-off threshold of 9.5 V
9.5 V DC to 28 V DC external power input with over-voltage protection

Receiver automatically turns on when connected to external power

Power over Ethernet (PoE)

44 V DC to 57 V DC, IEEE802.3af compliant device

Power consumption

6.0 W in rover mode with internal MSK Beacon receiver

Specifications

Trimble SPS361 Modular GPS Heading Receiver

Operation Time on Internal Battery

Rover	NA
Base station	NA
450 MHz systems	

Regulatory Approvals

FCC: Part 15 Subpart B (Class B Device) and Subpart C, Part 90
Canadian ICES-003. Cet appareil numérique de la classe B est conforme à la norme NMB-003 du Canada.
Canadian RSS-310, RSS-210, and RSS-119.
Cet appareil est conforme à la norme CNR-310, CNR-210, et CNR-119 du Canada.

R&TTE Directive: EN 301 489-1/-5/-17, EN 300 440, EN 300 328, EN 300 113, EN 60950, EN 50371

ACMA: AS/NZS 4295 approval
CE mark compliance
C-tick mark compliance
RoHS compliant
WEEE compliant

Communications

Lemo (Serial)	NA
Modem 1 (Serial)	26-pin D-sub, Serial 2, Full 9-wire RS232, using adaptor cable
Modem 2 (Serial)	26-pin D-sub, Serial 3, 3 wire RS-232, using adaptor cable
1PPS (1 pulse-per-second)	Available
Ethernet	Through a multi-port adaptor
Bluetooth wireless technology	Fully-integrated, fully-sealed 2.4 GHz Bluetooth module ⁴
Integrated radios (optional)	Fully-integrated, fully-sealed internal MSK Beacon radio
Channel spacing (450 MHz)	NA
450 MHz output power	NA
900 MHz output power	NA
Frequency approvals (900 MHz)	NA

External GSM/GPRS, cell phone support

Supported for direct-dial and Internet-based correction streams

Cell phone or GSM/GPRS modem inside controller

Internal MSK Beacon receiver

If internal MSK Beacon Radio is installed⁶
Frequency range 283.5–325.0 kHz
Channel spacing 500 Hz
MSK bit rate 50, 100, and 200 bps
Demodulation minimum shift key (MSK)

Correction data input
Correction data output
Data outputs

RTCM 2.x
Repeat RTCM from MSK Beacon or OmniSTAR VBS source
NMEA, GSOFF, 1PPS Time Tags

Specifications

Trimble SPS361 Modular GPS Heading Receiver

Receiver Upgrades

Not Upgradable

Notes

1 Receiver will operate normally to -40°C .

2 Accuracy and reliability may be subject to anomalies such as multipath, obstructions, satellite geometry, and atmospheric conditions. Always follow recommended practices.

3 Depends on SBAS system performance.

4 Bluetooth type approvals are country specific. For more information, contact your local Trimble office or representative.

5 Two of the supported antennas (See Antenna Options) must be connected for heading.

6 One of the antennas must be a GA530 for MSK Beacon signal reception.

Specifications subject to change without notice.

© 2009, Trimble Navigation Limited. All rights reserved. Trimble, the Globe & Triangle logo, and TSC2 are trademarks of Trimble Navigation Limited, registered in the United States and in other countries. CMR, CMR+, EVEREST, Maxwell, Micro-Centered, VRS, Zephyr, and Zephyr Geodetic are trademarks of Trimble Navigation Limited. The Bluetooth word mark and logos are owned by the Bluetooth SIG, Inc. and any use of such marks by Trimble Navigation Limited is under license. All other trademarks are the property of their respective owners. PN 022482-1615

Trimble Heavy and Highway Business Area

5475 Kellenburger Road
Dayton, Ohio 45424
USA
800-538-7800 (Toll Free)
+1-937-245-5154 Phone
+1-937-233-9441 Fax
www.trimble.com

Trimble Authorized Distribution Partner

GPS Integrated Systems, Inc
1414 West Belt North, Ste 110
Houston
TX 77043
713-973-8889
sales@gps-equipment.com
www.gps-equipment.com